



**MATERIAL SAFETY DATA SHEET**

**SMALL ARMS MARKER TRAINING AMMUNITION**

**CENTERFIRE PISTOL AMMUNITION**

**Federal Cartridge Company  
900 Ehlen Drive  
Anoka, Minnesota 55303**

**TELEPHONE: 763-323-2300  
PRODUCT SERVICE: 763-323-3706  
EMERGENCY PHONE NUMBER: 800-424-9300 (CHEMTREC)**

**Issue Date: February 2007**

=====

**SECTION #1 - PRODUCT IDENTIFICATION:**

<b>NON-TOXIC CENTERFIRE PISTOL PRODUCT FAMILY</b>		
Centerfire Metallic Cartridge Including The Following:		
<b>9mm Marking Round</b>		

**SECTION #2 - CHEMICAL COMPOUNDS:**

<b>CHEMICAL COMPOUNDS</b>			
	CAS NUMBER	TWA UNLESS OTHERWISE NOTED	
		OSHA PEL	ACGIH TLV
<b>Bullet</b> Polymer Jacket / glycerin core	9002-88-4 56-81-5	Not Listed 10 mg/m <sup>3</sup> Values apply to glycerin mist	Not Listed 10 mg/m <sup>3</sup> Values apply to glycerin mist
<b>Cartridge Body –</b> Aluminum	7429-90-5	Not Established for Aluminum Metal	Not Established For Aluminum Metal
<b>Primer -</b> Diazodinitrophenol	87-31-0	Not Established	Not Established
Tetracene	109-27-3	Not Established	Not Established
Barium Nitrate (as barium)	7440-39-3	0.5 mg/m <sup>3</sup>	0.5 mg/m <sup>3</sup>
*Aluminum	7429-90-5	15 mg/m <sup>3</sup> (5 mg/m <sup>3</sup> as respirable dust)	10 mg/m <sup>3</sup>
Nitrocellulose	9004-70-0	Not Established	Not Established

\* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR 372.

## DEFINITIONS OF ACRONYMS

OSHA PEL:	Occupational Safety and Health Administration's Permissible Exposure Limit.
ACGIH TLV:	American Conference of Governmental Industrial Hygienists' Threshold Limit Values.
TWA:	Time Weighted Average.
STEL:	Short Term Exposure Limit, the 15-minute exposure that should not be exceeded at any time during a workday.
CEILING:	The concentration that is not to be exceeded at any time during a workday.
CAS:	Chemical Abstracts Service number.

### SECTION #3 - PHYSICAL DATA

Boiling Point:	Not Applicable
Melting Point:	Not Applicable
Vapor Pressure:	Not Applicable
Density:	2.17 grams/cc
Solubility (Water):	None
Evaporation Rate:	Not Applicable
Percent Volatiles:	Not Applicable
Vapor Density (Air = 1):	Not Applicable

Appearance: Aluminum

Odor: None  
Odor Threshold: None

### SECTION #4 - FIRE FIGHTING & EXPLOSION DATA:

Flash Point (F):	Not Applicable
Auto Ignition Temperature (F):	Not Applicable
Upper Explosive Limits (Percent):	Not Applicable
Lower Explosive Limits (Percent):	Not Applicable

Fire & Explosion Hazards: May ignite if heated to 250 degrees F, independent of air. Unconfined ignited cartridges can produce low velocity metallic fragments that may cause eye injury or superficial skin wounds if unprotected by standard fire-fighter turnout gear.

Extinguishing Media: Water

Special Fire Fighting Instructions: Wear full fire-fighter protective gear including face shield or SCBA. Use wide fog pattern nozzle to stop any low velocity fragments. Use water to cool ordinary combustibles below ignition temperature.

## **SECTION #5A - EXPOSURE & EFFECTS -- INHALATION**

### **ROUTE OF EXPOSURE & EFFECTS - INHALATION**

Acute: Acute inhalation of smoke may produce mild throat and eye irritations.

Chronic: None known.

First Aid: Remove person to fresh air. Seek medical attention.

## **SECTION #5B - EXPOSURE & EFFECTS -- SKIN**

### **ROUTES OF EXPOSURE & EFFECTS - SKIN**

Acute: Contact with metal fumes may cause skin irritation.

Chronic: None known.

First Aid: Wash thoroughly with soap and water.

## **SECTION #5C - EXPOSURE & EFFECTS -- EYES**

### **ROUTES OF EXPOSURE & EFFECTS - EYES**

Acute: Contact with large volumes of smoke may cause minor eye irritation.

Chronic: None known.

First Aid: Remove person to fresh air. If foreign body is suspected, wash eyes in fresh water for 15 minutes, contact physician.

## **SECTION #5D - EXPOSURE & EFFECTS -- INGESTION**

### **ROUTE OF EXPOSURE & EFFECTS - INGESTION**

Acute: Ingestion is not a likely route of exposure.

Chronic: None known.

**Note:** Wash hands thoroughly with soap and water before eating or smoking.

First Aid: Ingestion is not a likely route of exposure. In case of ingestion, contact physician.

## **SECTION #5E - EXPOSURE & EFFECTS -- CARCINOGENESIS DATA**

N.T.P.: No

I.A.R.C.: No

OSHA:No

## **SECTION #5F – EXPOSURE & EFFECTS – COMMENTS**

Acute effects although not likely are not known.

## **SECTION #5G - AGGRAVATION OF PRE-EXISTING HEALTH CONDITIONS**

### **AGGRAVATION TO PRE-EXISTING HEALTH CONDITIONS**

None known.

## **SECTION #6 - REACTIVITY & POLYMERIZATION**

Stability: Stable under normal use conditions.

Conditions to Avoid: Individual cartridges may ignite if the primer is struck or if the cartridge is exposed to excess heat.

Incompatible Materials: Oils, Acids, Alkalies, Ammonia, and other corrosive materials.

Hazardous Decomposition  
Materials: Oxides of Nitrogen and Carbon.

Polymerization: Will not occur.

## **SECTION #7 - SPILLS, LEAKS & DISPOSAL PROCEDURES**

### **STEPS TO BE TAKEN - SPILLS:**

Avoid conditions detailed in Section #6. If container should rupture place all loose cartridges from broken shipping cases into a sturdy container, secure container carefully.

Waste Disposal Methods: Contact Manufacturer - Product Service (763) 323-3706.

## **SECTION #8 - SPECIAL PROTECTIVE EQUIPMENT**

Ventilation: Use in a well-ventilated area. Consult the current edition of ACGIH Industrial Ventilation Manual and/or NRA ventilation recommendations.

### **Protective Equipment:**

Eyes: Recommend protective eyewear conforming to ANSI Z-87.

Gloves: Not generally required.

Respirators: Use an approved respirator while cleaning range facilities if applicable exposure limits are exceeded.

Hearing Protection: Hearing protection recommended while discharging cartridges.

## **SECTION #9 - SPECIAL PRECAUTIONS -- STORAGE & HANDLING**

Store in a dry, cool area in the original container to assure performance. Keep out of the reach of children. Avoid striking the primer of unchambered cartridges. Remove ammunition from service if any of the following conditions have occurred:

1. Evidence of corrosion.
2. Physical damage.
3. Exposure to oil or spray type lubricants.

Avoid prolonged storage in leather cartridge carriers

## **SECTION #10 – TRANSPORTATION INFORMATION**

This material is a US Department of Transportation Hazardous Material.

US DOT Proper Shipping Name:	Cartridges, small arms
Hazard Classification:	1.4S
UN Identification Number:	UN0012
Packing Group:	II

=====

Although reasonable care has been taken in the preparation of this document, Federal Cartridge Company extends no warranties and makes no representation as to the accuracy or completeness of the information contained herein and assumes no responsibility regarding the suitability of this information for the user's intended purpose or the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose.